



*A NEW GENERATION  
OF RANGE HOODS*

**INSPIRED  
BY YOUR  
SENSES**

**ispira**  
VENMAR®



**INNOVATIONS**  
**INSPIRED BY YOUR SENSES**  
- ISPIRA





**Exclusive technologies. Revamped functions. Enhanced esthetics.**  
The new generation of Ispira range hoods features innovations that inspire and delight the senses. With their stylish design and trendy colors, Ispira hoods create a unique look to help personalize your kitchen.





## **SEE** *THE LIGHT*

**OUR EXCLUSIVE PURLED™ LIGHT SYSTEM IS MORE THAN JUST A BRILLIANT INNOVATION.**

Specially developed by Venmar and certified by Energy Star®, PURLED™ offers even, glare-free lighting across the entire cooking surface, just like in full daylight. This exclusive new LED system **boosts light output by 25%, distributes light 6 times better, improves energy efficiency by 88%, and extends the life of your light bulbs by up to 25 times\***. A truly sensational innovation!

- Choice of 4 light settings, including night light
- Comes with 2 LED bulbs (5.5 watt)

## **SMELL** *THE DIFFERENCE AT LAST*

**A NEW HYBRID FILTER FOR THE BEST OF BOTH WORLDS.**

The new hybrid filter is another Venmar innovation. The perfect combination of two filtering technologies, it **traps up to 28% more grease\***, at every ventilation speed. Say goodbye to unpleasant cooking odors and smell the Venmar difference.

- Full-size stainless steel filters
- Easy maintenance, dishwasher-safe

\* As compared to previous generation.

|4| |0| |\*|



## TOUCH THE CONVENIENCE

**FEATHER-TOUCH  
INTERFACE: THE PERFECT  
BLEND OF AVANT-GARDE  
DESIGN AND STATE-OF-  
THE-ART TECHNOLOGY.**

Ispira control was designed with one thing in mind—to make your life easier! And that's exactly what it does, with easy-to-clean and **easy-to-use LED backlighting feather-touch interface**, a built-in master on/off control, **and automatic last selected speed save function.**

- Heat Sentry™ mode that automatically adjusts ventilation to avoid overheating
- Delay off function for each speed (automatic shut-off after 5 minutes)
- Blue or white LED backlighting

## HEAR THE QUIETNESS

**AT LAST, AN ULTRA-  
SILENT BLOWER THAT  
DOESN'T DROWN OUT  
THE CONVERSATION.**

Whatever the blower speed, Ispira range hoods are amazingly silent: **58% quieter at normal speed\*\*.** The whisper-quiet blower is designed to allow you to cook and entertain at the same time—without having to raise your voice. Because silence is golden!

- Blower power up to 700 CFM
- 4 blower speeds for all your cooking needs

\*\* Data valid for IU600ES model.

## GET A TASTE FOR GREAT TRENDS

**INTERCHANGEABLE  
GLASS PANELS ADD  
A TOUCH OF BOLD  
COLOR TO YOUR DECOR.**


With our exclusive selection of **8 trendy colors, you can personalize your decor** to your own tastes. Our easily interchangeable glass panels offer you the **flexibility to create a unique style you can adapt as you please.** Feel like updating your decor? Simply change the glass panel for a new look. Be inspired!





## IC700

### Chimney range hood



Dimensions shown are in inches.  
Depth: 20 3/4 in.

### Specifications

- **30"** and **36"** wide
- **700 CFM** internal blower and **600 CFM** for the ENERGY STAR® qualified model\*
- **1.4 sones** at low speed and **2.0 sones** for the ENERGY STAR® qualified model
- **3 1/4" x 10"** vertical or horizontal discharge
- Suitable for **8' to 9'** high ceilings

### ISPIRA STANDARD

|                             | 30 in.      | 36 in.      |
|-----------------------------|-------------|-------------|
| Unit with white glass panel |             |             |
| White                       | IC70030WH   | IC70036WH   |
| ENERGY STAR® qualified unit | IC700ES30WH | IC700ES36WH |
| Brushed gray                | IC70030SS   | IC70036SS   |
| ENERGY STAR® qualified unit | IC700ES30SS | IC700ES36SS |
| Black                       | IC70030BL   | IC70036BL   |
| ENERGY STAR® qualified unit | IC700ES30BL | IC700ES36BL |

### ISPIRA CUSTOM

Feel like adding your own personal touch?  
Order the basic unit and the optional glass panel of your choice.

|                             | 30 in.      | 36 in.      |
|-----------------------------|-------------|-------------|
| Basic unit                  | IC70030WG   | IC70036WG   |
| ENERGY STAR® qualified unit | IC700ES30WG | IC700ES36WG |
| Optional glass panels       |             |             |
| White                       | SV09955WH   | SV09956WH   |
| Brushed gray                | SV09955SS   | SV09956SS   |
| Black                       | SV09955BL   | SV09956BL   |
| Orange                      | SV09955OR   | SV09956OR   |
| Lime                        | SV09955LM   | SV09956LM   |
| Purple                      | SV09955PU   | SV09956PU   |
| Red                         | SV09955RD   | SV09956RD   |
| Emerald                     | SV09955EM   | SV09956EM   |

### Options


|                                      |       |
|--------------------------------------|-------|
| Access code to limit CFM to 300      | 19329 |
| Flue extension for 10' high ceilings | 19323 |

\* Range hood airflow, tested by an independent laboratory designated by the Home Ventilating Institute (HVI), at 0.1 in. w.g. static pressure is 600 CFM for the IC700 model and 500 CFM for the IC700ES ENERGY STAR® qualified model.



## IU600ES

### Under-cabinet range hood



Dimensions shown are in inches.

### Specifications

- **30"** and **36"** wide
- **600 CFM** internal blower\*
- ENERGY STAR® qualified
- **1.0 sone** at low speed
- **3 1/4" x 10"** vertical or horizontal discharge

### ISPIRA STANDARD

|                       | 30 in.      | 36 in.      |
|-----------------------|-------------|-------------|
| Unit with glass panel |             |             |
| White                 | IU600ES30WH | IU600ES36WH |
| Brushed gray          | IU600ES30SS | IU600ES36SS |
| Black                 | IU600ES30BL | IU600ES36BL |

### ISPIRA CUSTOM

Feel like adding your own personal touch?  
Order the basic unit and the optional glass panel of your choice.

|                       | 30 in.      | 36 in.      |
|-----------------------|-------------|-------------|
| Basic unit            | IU600ES30WG | IU600ES36WG |
| Optional glass panels |             |             |
| White                 | SV09953WH   | SV09954WH   |
| Brushed gray          | SV09953SS   | SV09954SS   |
| Black                 | SV09953BL   | SV09954BL   |
| Orange                | SV09953OR   | SV09954OR   |
| Lime                  | SV09953LM   | SV09954LM   |
| Purple                | SV09953PU   | SV09954PU   |
| Red                   | SV09953RD   | SV09954RD   |
| Emerald               | SV09953EM   | SV09954EM   |


### Options

|                                 |       |
|---------------------------------|-------|
| Access code to limit CFM to 300 | 19329 |
|---------------------------------|-------|

\* Range hood airflow, tested by an independent laboratory designated by the Home Ventilating Institute (HVI), at 0.1 in. w.g. static pressure is 500 CFM.

## IB700

### Built-in range hood



Dimensions shown are in inches.  
Depth: 20 3/4 in.

### Specifications

- **30"** and **36"** wide
- **700 CFM** internal blower\*
- **1.4 sones** at low speed
- **3 1/4" x 10"** vertical or horizontal discharge

### ISPIRA CUSTOM

Feel like adding your own personal touch?  
Order the basic unit and the optional glass panel of your choice.

|                       | 30 in.    | 36 in.    |
|-----------------------|-----------|-----------|
| Basic unit            | IB70030WG | IB70036WG |
| Optional glass panels |           |           |
| White                 | SV09955WH | SV09956WH |
| Brushed gray          | SV09955SS | SV09956SS |
| Black                 | SV09955BL | SV09956BL |
| Orange                | SV09955OR | SV09956OR |
| Lime                  | SV09955LM | SV09956LM |
| Purple                | SV09955PU | SV09956PU |
| Red                   | SV09955RD | SV09956RD |
| Emerald               | SV09955EM | SV09956EM |

### Options


|                                 |       |
|---------------------------------|-------|
| Access code to limit CFM to 300 | 19329 |
|---------------------------------|-------|

\* Range hood airflow, tested by an independent laboratory designated by the Home Ventilating Institute (HVI), at 0.1 in. w.g. static pressure is 600 CFM.



## IS700

### Island range hood



Dimensions shown are in inches.  
Depth: 22 in.

### Specifications

- **36"** wide
- **700 CFM** internal blower\*
- **1.2 sones** at low speed
- **8"** round duct (vertical discharge)
- Suitable for **8' to 9'** high ceilings

### ISPIRA STANDARD

**36 in.**

| Unit with glass panels                    |           |
|---|-----------|
| <input type="checkbox"/> White (2)        | IS70036WH |
| <input type="checkbox"/> Brushed gray (2) | IS70036SS |
| <input type="checkbox"/> Black (2)        | IS70036BL |

### ISPIRA CUSTOM

Feel like adding your own personal touch?  
Order the basic unit and the optional glass panel of your choice.

| 36 in.                                |                 |           |
|---------------------------------------|-----------------|-----------|
| Basic unit                            | IS70036WG       |           |
| Optional glass panels                 | Front (control) | Rear      |
| <input type="checkbox"/> White        | SV09956WH       | SV09957WH |
| <input type="checkbox"/> Brushed gray | SV09956SS       | SV09957SS |
| <input type="checkbox"/> Black        | SV09956BL       | SV09957BL |
| <input type="checkbox"/> Orange       | SV09956OR       | SV09957OR |
| <input type="checkbox"/> Lime         | SV09956LM       | SV09957LM |
| <input type="checkbox"/> Purple       | SV09956PU       | SV09957PU |
| <input type="checkbox"/> Red          | SV09956RD       | SV09957RD |
| <input type="checkbox"/> Emerald      | SV09956EM       | SV09957EM |

### Options

|                                      |       |
|--------------------------------------|-------|
| Access code to limit CFM to 300      | 19329 |
| Flue extension for 10' high ceilings | 19324 |
| Remote control                       | 21233 |

\* Range hood airflow, tested by an independent laboratory designated by the Home Ventilating Institute (HVI), at 0.1 in. w.g. static pressure is 600 CFM.



## SINGLE ISLAND

## IK700


### Island or chimney range hood



## WALL MOUNTED



## DOUBLE ISLAND



Dimensions shown are in inches.  
Depth: 16 in.

### Specifications

- **16"** wide
- **700 CFM** internal blower\*
- **1.2 sones** at low speed
- **8"** round duct (vertical discharge)
- Suitable for **8' to 9'** high ceilings

### ISPIRA STANDARD

**16 in.**

| Unit with glass panels                    |           |
|---|-----------|
| <input type="checkbox"/> White (2)        | IK70016WH |
| <input type="checkbox"/> Brushed gray (2) | IK70016SS |
| <input type="checkbox"/> Black (2)        | IK70016BL |

### ISPIRA CUSTOM

Feel like adding your own personal touch?  
Order the basic unit and the optional glass panel of your choice.

| 16 in.                                |                 |           |
|---------------------------------------|-----------------|-----------|
| Basic unit                            | IK70016WG       |           |
| Optional glass panels                 | Front (control) | Rear      |
| <input type="checkbox"/> White        | SV09958WH       | SV09959WH |
| <input type="checkbox"/> Brushed gray | SV09958SS       | SV09959SS |
| <input type="checkbox"/> Black        | SV09958BL       | SV09959BL |
| <input type="checkbox"/> Orange       | SV09958OR       | SV09959OR |
| <input type="checkbox"/> Lime         | SV09958LM       | SV09959LM |
| <input type="checkbox"/> Purple       | SV09958PU       | SV09959PU |
| <input type="checkbox"/> Red          | SV09958RD       | SV09959RD |
| <input type="checkbox"/> Emerald      | SV09958EM       | SV09959EM |

### Options

|                                      |       |
|--------------------------------------|-------|
| Access code to limit CFM to 300      | 19329 |
| Flue extension for 10' high ceilings | 19325 |
| Remote control                       | 21233 |

\* Range hood airflow, tested by an independent laboratory designated by the Home Ventilating Institute (HVI), at 0.1 in. w.g. static pressure is 540 CFM.

**CHOOSE**  
AN ISPIRA  
RANGE HOOD

**INSPIRED**  
**BY YOUR SENSES**

*ispira.ca*

Venmar Ventilation inc.  
550 boulevard Lemire  
Drummondville, Quebec J2C 7W9, Canada  
1-800-567-3855 • [ispira.ca](http://ispira.ca)

**ispira**  
VENMAR®